

## Discrete Downlight - LL-1003-3W60-70S10W8-200

www.lumenall.com.au



### General Specifications

|               |                    |
|---------------|--------------------|
| Product Name  | Discrete Downlight |
| Product Range | Discrete Downlight |
| Product Code  | LL-1003            |
| IP Rating     | IP44 Room side     |
| Finish        | white              |
| Dimensions    | 70mm               |

### Additional Specifications

|             |                  |
|-------------|------------------|
| Optics      | 60               |
| Accessories |                  |
| Mounting    | Recessed springs |
| Diffuser    | Clear            |
| UGR         | <19              |

### Supplier Information

|                |                   |
|----------------|-------------------|
| Distributor    | Lumenall Lighting |
| Contact Person | Sean Boxshall     |
| Lead Time      | 4 - 12 Weeks      |
| Warranty       | 5 Years           |

### LED

|                        |                                                   |
|------------------------|---------------------------------------------------|
| Lamp Type              | Cree CXA1507 COB                                  |
| Power                  | 10w                                               |
| Colour Temperature     | 3000k                                             |
| CRI                    | 80                                                |
| Colour Deviation       | SDCM < 3                                          |
| Absolute Luminous Flux | Upto 90lm-w                                       |
| Lifespan               | Calculated L70 - 60,000h<br>Reported L70 > 39,000 |

### Electronic Control Gear

|                   |                               |
|-------------------|-------------------------------|
| Type              | Lumenall Driver - Gen 2       |
| Rating            | 200ma                         |
| Built in / Remote | Remote / Dimmable (Phase cut) |
| Power Factor      | > 0.95                        |

### Additional Information

DALI options available, Tridonic driver.